



*** MINIMUM FRAMING DIMENSIONS**

| Models | A | | B | C | | D | E | F | G | H | I | J | |
|---------|-----------------------|-----------------------|------------------------|-----------------------|-----------------------|-----------------------|----------------------|-------------------|----------------------|------------------|--------------------|--------------------|-----|
| | DVP Pipe | SLP Pipe | Rough Opening (Height) | **DVP Pipe | SLP Pipe | Rough Opening (Width) | Clearance to Ceiling | Combustible Floor | Combustible Flooring | Behind Appliance | Sides of Appliance | Front of Appliance | |
| | Rough Opening (Width) | Rough Opening (Width) | | Rough Opening (Depth) | Rough Opening (Depth) | | | | | | | | |
| 350X-AU | in. | 10 | 8-5/8 | 32-3/4 | 16-1/4 | 16-1/4 | 34 | 32 | 0 | 0 | 1/2 | 1/2 | 36 |
| | mm | 254 | 219 | 832 | 413 | 413 | 864 | 813 | 0 | 0 | 13 | 13 | 914 |
| 550X-AU | in. | 10 | 8-5/8 | 34-3/4 | 16-1/4 | 16-1/4 | 37 | 32 | 0 | 0 | 1/2 | 1/2 | 36 |
| | mm | 254 | 219 | 882 | 451 | 451 | 940 | 813 | 0 | 0 | 13 | 13 | 914 |

* Adjust framing dimensions for interior sheathing (such as sheetrock)

C** Add 12 in. (305 mm) when rear venting with one 90° elbow.

Figure 3.4 Clearances to Combustibles